


## Angle Corrected Brake Beams



MULTI-CATEGORY PRODUCT

The A.Stucki Angle Corrected Brake Beam is lightweight and reliable at high speeds. It ensures even shoe wear and extends the life of the strut/beam.



All Stucki Brake Heads are replaceable. Quick Change Beams and Cast Iron Beams also available.





AAR approved and available in 18,000 lb. and 24,000 lb. capacity for composition, tread conditioning, or cast iron shoes.

## **BENEFITS**

- Replaceable angle corrected brake heads
- Rugged consistent design
- · Diagonally corrected beams reduce shoe wear
- · User friendly reversible strut, easily switched from left to right
- Durable & light
- Easily installed and inspected
- Hardened pin holes for extended life; no bushings to loosen in service
- · Fatigue & vibration resistant
- · Reduced maintenance cost of burnt brake heads
- Hanger beams also available

## LIGHT WEIGHT AND RELIABLE

The A.Stucki Angle Corrected Brake Beam is light weight and reliable at high speeds. The optimized brake shoe angle will ensure even shoe wear. The increased wear areas in the brake lever slot extend the life of the strut/beam.

## MAXIMIZE YOUR RETURN ON INVESTMENT

We know your time is best spent doing what you do best... moving freight. You need a partner who can ensure that your cars are reliable and exceed the expectations of your customers. Maximize your return on investment by contacting us today to discuss the beam that pays for itself.

www.stucki.com
Ofc: 412-424-0560
sales@stucki.com
360 Wright Brothers Dr. Moon Township, PA 15108

A.STI		A.STI		A.STI		A.STI	
	A.STI		A.STI		A.STI		A.STL
A.STI		A.STI		A.STI		A.STI	
	A.STI		A.STI		A.STI		A.STL
A.STI				A.STI		A.STI	
	A.STI		A.STI		A.STI		A.STL
A.STI		A.STI		A.STI		A.STI	
	A.STI		A.STI		A.STI		A.STL
A.STI		A.STI		A.STI		A.STI	
	A.STI		A.STI		A.STI		A.STL
A.STI		A.STI		A.STI		A.STI	
	A.STI		A.STI		A.STI		A.STL
A.STI		A.STI		A.STI		A.STI	
	A.STI		A.STI		A.STI		A.STL
A.STI				A.STI		A.STI	
			A.STI		A.STI		A.STL
A.STI		A.STI		A.STI			
	A.STI		A.STI		A.STI		A.STL
A.STI		A.STI		A.STI		A.STI	
	A.STI		A.STI		A.STI		A.STL
A.STI		A.STI		A.STI		A.STI	