

Quick Connect Hose Barb



TANK TRAILER

Stucki's 2-Inch reinforced cammed female hose barb provides a secure, leak-free connection that stands up to tough transfer conditions while allowing for fast, efficient unloading with minimal downtime.



Replacement Parts Kit Available

Part Number: HS2KRFPKIT



Not sure if your commodity is compatible?
Review our full chemical compatibility chart at:
www.stucki.com/UHMWcompchart



2-Inch Reinforced Female Hose Barb (Cammed)

Part Number: HS2KRFP03A

FEATURES & BENEFITS

- Stainless steel reinforcement enhances durability and long-term reliability.
- UHMWPE construction resists corrosion and abrasion in demanding transfer environments.
- Lightweight design allows for quick, easy attachment and removal.
- Rated to 150 psi, suitable for unloading tank trucks and railcars.
- Performs reliably across a wide service temperature range from -30°F to 150°F.
- Available in a 2-inch size
- Stainless steel cam arms securely lock the hose in place.
- Replaceable 1/4-inch EPDM or Viton gasket ensures a tight, leak-free seal.

CONNECT WITH CONFIDENCE

This reinforced hose barb enables faster, safer unloading with a secure, quick-connect design that maintains a leak-free seal under pressure. Operators gain confidence during tank truck and railcar transfers while reducing downtime and keeping the transfer process clean and efficient.